



ATC 用ボーリングバー カートリッジ式 A 型 (BCA) BT50

ご注文時は、UNIT CODEにて E(鉄用)orF(鉄/用) のいずれかのマイクロユニットチップをご選定下さい。

CODE	FIG.	D		L	M1	C1	C2	C3	H1	E1	E2	UNIT CODE	質量 kg			
		MIN	MAX													
BT50-BCA13. 5-120	1	13.5	16.0	120	67	12	13	44	15	10	0.2	M1B212EorM1B212F	4.0			
-BCA13. 5-195				195						85			5.0			
BT50-BCA14. 5-120		14.5	17.0	120	86	16	14		18	10			4	4.0		
-BCA14. 5-195				195						85				5.0		
BT50-BCA16 -120		16.0	22.5	120	73	14	15		23	4		6	4.0			
-BCA16 -195				195						79			5.0			
BT50-BCA19 -135		19.0	23.0	135	86	16	18		24	6		81	4.0			
-BCA19 -210				210						81			5.0			
BT50-BCA23 -150		23.0	29.0	150	105	19	22		30	2		77	4.0			
-BCA23 -225				225						77			5.0			
BT50-BCA29 -165		29.0	41.0	165	115	25	28		41	7		67	4.5			
-BCA29 -225				225						67			5.5			
BT50-BCA38 -165		38.0	49.0	165	172	33	35		55	7		10	4.5			
-BCA38 -225				225			37			10			5.0			
BT50-BCA46 -165		46.0	66.0	165	115	38	41		55	45		7	6	0.2	M5A2EorM5A2F	5.5
-BCA46 -225				225			44					-				-
-BCA46 -255				255			44					55				6
BT50-BCA62 -180		2	62.0	87.0	180	137	-		-	-		-	-	0.2	M7A2EorM7A2F	7.0
-BCA62 -240	1	240			184	51	57	70	60	13	8.5					
-BCA62 -330	1	330			280	51	59	70	60	7	8.5					
BT50-BCA83 -165	2	83.0	108.0	165	122	-	-	-	-	-	0.2	M7A2EorM7A2F	6.5			
-BCA83 -240	1			240	190	63	70	-	70	7			9.0			
-BCA83 -345	1			345	302	63	76	90	70	-			12.0			
BT50-BCA98 -165	2	98.0	142.0	165	122	-	-	-	-	-	0.2	M10A2EorM10A2F	8.5			
-BCA98 -240	1			240	197	83	-	-	-	-			11.5			
-BCA98 -345	1			345	302	83	92	-	85	220			17.0			
BT50-BCA132 -210	3	132.0	176.0	210	-	108	-	-	65	-	0.2	M10A2EorM10A2F	12.0			
-BCA132 -315				315									18.5			
BT50-BCA166 -225		166.0	210.0	225	-	142	-	-	70	-			13.0			
-BCA166 -315				315									18.5			
※ BT50-BCA200 -210	3	200.0	244.0	210	-	176	-	-	75	-	20.0					